

GENERAL:

The surface drainage system shall be 6000P Series Catch Basin, as manufactured by FoodSafe Drains.

MATERIALS:


- T304 Stainless Steel
- T316 Stainless Steel

LOAD CLASS: E

INSTALLATION:

The 6000P Series Catch Basin shall be installed in accordance with the manufacturer's installation instructions and recommendations.

TYPICAL PROFILE OF A 6000P SERIES CATCH BASIN



	TOP WIDTH (mm)	TOP LENGTH (mm)	BOTTOM WIDTH (mm)	BOTTOM LENGTH (mm)	HEIGHT (mm)	OUTLET SIZE (mm)
6000P SS SMALL 152 X 305	314	162	140	292	310	102
6000P SS LARGE 152 X 305	314	162	140	292	411	102
6000P SS SMALL 305 X 305	314	314	292	292	310	102 or 152
6000P SS LARGE 305 X 305	314	314	292	292	411	102 or 152

NOTE: Available in 3 different design options according to the drain length. Flange - 5 catch basin - up to 4 drain sections (13 x 305 x 310). Flange - 8 catch basin - up to 7 drain sections (13 x 305 x 310). Flange - 11 catch basin - up to 10 drain sections (13 x 305 x 411). Custom sizes are available as required. Solid Lid with a holes is our standard design, also custom lids available as required. SCH40 pipes are standard design, also SCH10 available as required. Optionally available end, side outlets. End or middle catch basin is our standard. Also available in "TEE" or cross connection catch basin. Available in Maglock/non Maglock design options.

Specifying engineer is responsible for concrete encasement and reinforcing based upon application and local codes. FoodSafe Drains reserves the right to change the product and specifications without notice.